



Mfrs. of Cleaning Automation Products

## RING BLOWER - TECHNICAL SPECIFICATIONS

Model	Impeller Fan	Frequency	Rated	Voltage	Rated	Max	Rated	Rated	Inlet	Noise	Weight
			Power		current	airflow	Inlet pressure	outlet pressure	Outlet Size		
	Stage	HZ	KW	V	A	m3/h	mbar	mbar	mm	dB(A)	Kg
025A	Single	50	0.25	230	1	50	-110	110	30	40	7
05A	Single	50	0.4	415	1.5Y	80	-120	130	38	53	10
		50	0.4	230	3	80	-120	130	38	53	10
1A	Single	50	0.75	415	2.2Y	145	-120	120	47	63	13
		50	0.75	230	4.5	145	-120	120	47	63	13
1B	Double	50	0.75	415	2.2Y	88	-210	240	38	55	14
		50	0.75	230	4.5	88	-210	240	38	55	14
085A	Single	50	0.85	415	2.5Y	145	-160	160	47	63	15
		50	0.85	230	5.4	145	-160	160	47	63	15
105A	Single	50	1.3	415	3.5Y	145	-170	200	58	63	17
		50	1.3	230	7.3	210	-170	170	58	63	17
2A	Single	50	1.6	415	4.3Y	210	-200	190	58	64	21
		50	1.6	230	9	210	-200	190	58	64	21
2B	Double	50	1.6	415	4.3Y	150	-280	280	47	66	24
3A	Single	50	2.2	415	5.0Y	305	-200	200	58	68	27
		50	2.2	230	10	270	-230	250	58	68	27
3B	Double	50	2.2	415	5.6Y	150	-330	440	47	66	27
5A	Single	50	4	415	9.0Δ	400	-290	330	58	69	42
5B	Double	50	4	415	5.8Y	230	-390	490	58	72	43
7A	Single	50	5.5	415	12.9Δ	750	-370	570	72	80	65
7B	Double	50	5.5	415	13.3Δ	320	-440	500	58	73	70
10A	Single	50	7.5	415	16.7Δ	800	-380	570	72	80	68
10B	Double	50	7.5	415	16.7Δ	350	-440	570	58	73	77
15A	Single	50	12.5	415	28	1050	-290	280	110	74	132